moooi

Iconic Eyes

BERNHARD DESSECKER



The first sparkle of this great idea was inspired by iconic automotive headlights. They have been modified to design a grand pendant light with a classy, powerful impact for the foyer of the Bavarian National Museum in Germany. The light's oval design is modern with a classic touch. It generates a precious ambient glow enhanced by bright rings of light and is produced in two sizes. Glorious and breathtaking in appearance, it consists of numerous lenses and a constellation of LED lights.

Detailing



Iconic Eyes consists of the characteristic headlights of a BMW MINI, which are placed in an oval shape and create an atmospheric glow.

Colours



Black Chrome

Iconic Eyes / Iconic Eyes 161

Dimensions

77cm | 30.3"



Product

width 77cm | 30.3" HEIGHT 119cm | 46.9" DEPTH 77cm | 30.3" DIAMETER 77cm | 30.3" WEIGHT NETTO 70kg | 154.32|bs **Packaging**

width $96 \text{cm} \mid 37.8"$ Height $164 \text{cm} \mid 64.6"$ Cubage $1.51 \text{m}^3 \mid 53.38 \text{ft}^3$ Length $96 \text{cm} \mid 37.8"$ Weight $100 \text{kg} \mid 220.46 \text{lbs}$

Technical CE

MATERIAL

PE Sphere with PC and ABS lenses and chrome detailing

ENERGY LABEL

В

LIGHTSOURCE INCLUDED

Yes

SHAPEAbstract

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Transparent with tinned cores

CANOPY

White metal rectangle

CRI 88

DIMMING & LIGHTING CONTROL

1-10V

See last page for more information about the dimming possibilities.

 ϵ

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

161

INPUT VOLTAGE

MAX POWER CONSUMPTION

220W

LIFETIME

50000 hours

CABLE LENGTH

1000cm | 393.7"

COLOUR TEMPERATURE

2700 K

LIGHT ОПТРИТ 7019 lm

Technical UL

MATERIAL

PE Sphere with PC and ABS lenses and chrome detailing

ENERGY LABEL

В

LIGHTSOURCE INCLUDED

Yes

SHAPEAbstract

FREQUENCY 50/60

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Transparent with tinned cores

CANOPY

White metal rectangle

CRI 88

DIMMING & LIGHTING CONTROL

1-10V

See last page for more information about the dimming possibilities.



LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

161

INPUT VOLTAGE 100-264V

MAX POWER CONSUMPTION

220W

LIFETIME

50000 hours

CABLE LENGTH 1000cm | 393.7"


COLOUR TEMPERATURE

2700 K

LIGHT OUTPUT 7019 lm

Iconic Eyes / Iconic Eyes 85

Dimensions



Product

width 60cm | 23.6" HEIGHT 88cm | 34.6" DEPTH 60cm | 23.6" DIAMETER 60cm | 23.6" WEIGHT NETTO 35kg | 77.16lbs

Packaging

width 86cm | 33.9" Height 136cm | 53.5" Cubage 1.01m³ | 35.52ft³ Length 86cm | 33.9" Weight 90kg | 198.42lbs

Technical CE

MATERIAL

PE Sphere with PC and ABS lenses and chrome detailing

ENERGY LABEL LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED NUMBER OF LIGHTSOURCES

Yes

SHAPE INPUT VOLTAGE
Abstract 100-264V

FREQUENCY MAX POWER CONSUMPTION

50/60 110W

LAMPHOLDER LIFETIME

LED (Solid state) 50000 hours

CABLE COLOURCABLE LENGTHTransparent with tinned cores400cm | 157.5"

CANOPY COLOUR TEMPERATURE

White metal rectangle 2700 K

 CRI
 LIGHT OUTPUT

 88
 3706 lm

DIMMING & LIGHTING CONTROL

1-10V

See last page for more information about the dimming possibilities.

ϵ

Technical UL

MATERIAL

PE Sphere with PC and ABS lenses and chrome detailing

ENERGY LABEL LIGHTSOURCE TYPE

B LED

LIGHTSOURCE INCLUDED NUMBER OF LIGHTSOURCES

Yes 85

SHAPE INPUT VOLTAGE
Abstract 100-264V

FREQUENCY MAX POWER CONSUMPTION

50/60 110W

LAMPHOLDER LIFETIME

LED (Solid state) 50000 hours

CABLE COLOUR

Transparent with tinned cores

CANOPY

White metal rectangle

CRI

88

00

DIMMING & LIGHTING CONTROL

1-10V

See last page for more information about the dimming possibilities.



CABLE LENGTH

400cm | 157.5"

COLOUR TEMPERATURE

2700 K

LIGHT OUTPUT

3706 lm

Dimming & Lighting Control

1-10V

The luminaire is dimmable by using an either internally mounted or externally placed 1-10V dimmer switch. 1-10V is a dimming system widely used in some parts of the world, for example in North-America. This method will need its own wiring. Dimming quality is perfect, without flicker, the range can be limited and the luminaire cannot be dimmed to off. To turn off the luminaire a switch is needed.

Compatible models: Iconic Eyes 161 CE, Iconic Eyes 161 UL, Iconic Eyes 85 CE, Iconic Eyes 85 UL