


# Lula UP Bracket 150

LL15304KN


**Lombardo.**



## Technical information:

|                                    |                        |
|------------------------------------|------------------------|
| Installation:                      | Wall                   |
| Material:                          | Aluminium              |
| Finish:                            | Corten                 |
| Treatment:                         | Sea Treatment          |
| Diffuser type:                     | Frosted glass          |
| Lamp type:                         | LED                    |
| Energy performance class:          | F                      |
| Colour temperature:                | 4000K                  |
| CRI:                               | >80                    |
| LB Factor:                         | L80B50 - 50.000h       |
| Photobiological risk:              | RG0                    |
| Power consumption (Watt):          | 12                     |
| Lumen:                             | 1330                   |
| Real Lumen:                        | 1100                   |
| Power supply:                      | ✓ integrated           |
| LED:                               | AC DIRECT              |
| Insulation class:                  | ⊕ CL.I                 |
| Power cable:                       | 1 m H05RN-F 3x1        |
| Type of protection:                | <b>IP 65</b>           |
| Resistance to breakage:            | <b>IK 03 0,35J xx2</b> |
| Standards and Marks of Conformity: | CE UK CA               |
| Dimming                            | Phase cut              |

Glass diffuser.



# Lula UP Bracket 150

LL15304KN

**Lombardo.**



# Lula UP Bracket 150

LL15304KN

**Lombardo.**

## Photometric curves:

