



### Technical information:


|                                    |                          |
|------------------------------------|--------------------------|
| Installation:                      | Ground                   |
| Material:                          | Aluminium                |
| Finish:                            | Green Anodized Aluminium |
| Treatment:                         | Anodization              |
| Diffuser type:                     | Serigraphed glass        |
| Optics:                            | 25°                      |
| Lamp type:                         | LED                      |
| Energy performance class:          | E                        |
| Colour temperature:                | 3000K                    |
| CRI:                               | >80                      |
| LB Factor:                         | LM80B20 - 50.000h        |
| Photobiological risk:              | RG0                      |
| Power consumption (Watt):          | 20                       |
| Lumen:                             | 2200                     |
| Real Lumen:                        | 1560                     |
| Power supply:                      | ⊗ not included           |
| LED:                               | 24V                      |
| Insulation class:                  | ⚡ CL.III                 |
| Type of protection:                | <b>IP 66</b>             |
| Resistance to breakage:            | <b>IK 07 2J xx5</b>      |
| Standards and Marks of Conformity: | CE UK CA                 |

Optic D not available for Honeycomb version. AC-Direct version cable: 1m H05RN-F 3x1. Cable 24V version: 1m H05RN-F 2x0.75.





## Installation images:



### Photometric curves:

