



CorePro GLASS LED candles and lusters

CorePro LEDCandleND6.5-60W B35 E14827FRG

Featuring a classic heritage design, these filament LED candle combines the familiar shapes of classic incandescent bulbs with the benefits of long-lasting LED technology. The LED candle bulb, a very easy choice for people who are looking for a retrofit LED replacement, the LED candle provides 90% energy savings compared with conventional lamps. CorePro Glass LED bulbs provide excellent quality of light for stairway lighting. The LED candle bulb offers a lifetime of 15,000 hours to reduce maintenance costs.

Product data

General Information	
Lighting Technology	LED
Flux measurement reference	Sphere
Switching Cycle	20,000
Nominal lifetime	15,000 hour(s)
Cap-Base	E14 [E14]
Light Technical	
Color Code	827 [CCT of 2700K]
Luminous Flux	806 lumen
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	124.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Flickering value (PstLM)	1

Stroboscopic effect value (SVM)	0.9
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	6.5 W
Lamp Current (Nom)	50 mA
Wattage Equivalent	60 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.55
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	55 °C

CorePro GLASS LED candles and lusters

Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Bulb Finish	Frosted
Bulb Shape	B35 [B 35mm]


Approval and Application

Energy Efficiency Class	E
Energy Consumption kWh/1000 h	7 kWh
EPREL Registration Number	387443
CE mark	Yes
EU RoHS compliant	Yes

Product Data



Full product code	871951434750200
Order product name	CorePro LEDCandleND6.5-60W B35 E14827FRG
Order code	929002028292
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material number (12NC)	929002028292
Full product name	CorePro LEDCandleND6.5-60W B35 E14827FRG
EAN/UPC - Case	8719514347519

Dimensional drawing



Product	D	C
CorePro LEDCandleND6.5-60W B35 E14827FRG	35 mm	97 mm

Photometric data




General uniform lighting - CorePro LEDCandleND6.5-60W B35 E14827FRG

Spectral Power Distribution Colour - CorePro LEDCandleND6.5-60W B35 E14827FRG


CorePro GLASS LED candles and lusters

Photometric data




Light Distribution Diagram - CorePro LEDCandleND6.5-60W B35 E14827FRG

Lifetime



Lumen Maintenance Diagram - CorePro LEDCandleND6.5-60W B35 E14827FRG



Life Expectancy Diagram - CorePro LEDCandleND6.5-60W B35 E14827FRG

