

m o o o i

# Plant Chandelier

KRANEN/GILLE



The philosophy behind the Plant Chandelier, designed by Kranen/Gille, is the imitation of nature's structures while indulging in the poetry of their beauty. Inspired by the linear patterns of Karl Blossfeldt's plant photography, and unrestricted by cables or wires, the Plant Chandelier is free to elegantly bloom towards the ceiling. Its silhouette follows the anatomy of sun-kissed tree branches, with a golden glow, which converges into frosted domes of light.

---


## *Detailing*



The Plant Chandelier captivates the architectural uniformity in nature's design, with its branches that grow and spread in definite directions.

---

## *Colours*



Brass


# Plant Chandelier

## Dimensions

90cm | 35.4"



78cm | 30.7"



80cm | 31.5"



105cm | 41.3"

## Product

**WIDTH** 90cm | 35.4"

**HEIGHT** 80cm | 31.5"

**DEPTH** 78cm | 30.7"

**WEIGHT NETTO** 20kg | 44.09lbs

## Packaging

**WIDTH** 92cm | 36.2"

**HEIGHT** 91cm | 35.8"

**CUBAGE** 0.84m<sup>3</sup> | 29.57ft<sup>3</sup>

**LENGTH** 100cm | 39.4"

**WEIGHT** 27.5kg | 60.63lbs

## Technical CE

### MATERIAL

Steel frame, glass diffusers

### ENERGY LABEL

A

### LIGHTSOURCE TYPE

LED

### LIGHTSOURCE INCLUDED

Yes

### NUMBER OF LIGHTSOURCES

8

### INPUT VOLTAGE

220-240V

### FREQUENCY

50/60

### MAX POWER CONSUMPTION

16W

### LAMPHOLDER

LED (Solid state)

### LIFETIME

50000 hours

### CABLE COLOUR

Transparent with tinned cores

### CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

### CANOPY

Matching steel cylinder

### COLOUR TEMPERATURE

2700 K

### CRI

80

### LIGHT DIRECTION

All directions

### LIGHT OUTPUT

1318 lm

### EEI

0.17

### EFFICIENCY

82.38 lm/W

### DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.



---

## Technical UL

### MATERIAL

Steel frame, glass diffusers

### ENERGY LABEL

A

### LIGHTSOURCE TYPE

LED

### LIGHTSOURCE INCLUDED

Yes

### NUMBER OF LIGHTSOURCES

8

### INPUT VOLTAGE

110-130V

### FREQUENCY

50/60

### MAX POWER CONSUMPTION

16W

### LAMPHOLDER

LED (Solid state)

### LIFETIME

50000 hours

### CABLE COLOUR

Transparent with tinned cores

### CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

### CANOPY

Matching steel cylinder

### COLOUR TEMPERATURE

2700 K

### CRI

80

### LIGHT DIRECTION

All directions

### LIGHT OUTPUT

1318 lm

### EEI

0.17

### EFFICIENCY

82.38 lm/W

### DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

*See last page for more information about the dimming possibilities.*



## *Dimming & Lighting Control*

### *Mains, Trailing edge, Reverse phase*

The luminaire is dimmable by using an external Electronic Low Voltage dimmer. The dimmer is usually mounted on an existing wall socket and there is no need to change your home's wiring. On the dimmer it should show that it is a LED dimmer, suitable for 5 Watts or lower and C-type capable. Dimming is less fluent and can come with some flicker, a beep or a buzz.

Compatible models: Plant Chandelier CE, Plant Chandelier UL

---