




w151 Extra large pendant s1 3000 K / traffic white



w151 Extra large pendant s2 3000 K / traffic white



w151 Extra large pendant s1



Technical information

Physical	
Material	Shade: aluminium Canopy: polycarbonate
Optics	Diffuser: acrylic
IP rating	20
Protection class	I

LED	
Light source	Integrated LED
Life time expectancy	L80 / 50,000 h
CRI Colour Rendering Index	≥ 90
Standard deviation of colour matching	3-step MacAdam
Replaceable by a professional	

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wästberg Lighting AB apply.

Article-specific information

Version	s1
Mounting	Ceiling suspended
LED Colour temperature (CCT) / Luminous flux	2700 K / 3910 lm 3000 K / 4096 lm
Voltage / System power	220–240 V / 46 W
Efficacy	88 lm / W
Light control	DALI dim-Push dim
Net weight	5.5 kg
Packaging dimensions	L55 × W55 × H134 cm (0,4 m ³)
Gross weight	10 kg


2700 K Colour temperature (CCT)	
Traffic White (RAL 9016)	
Jet black (RAL 9005)	
Red orange (RAL 2001)	
Carmine red (RAL 3002)	
Purple red (RAL 3004)	
Raw brushed	

3000 K Colour temperature (CCT)	
Traffic white (RAL 9016)	
Jet black (RAL 9005)	
Red orange (RAL 2001)	
Carmine red (RAL 3002)	
Purple red (RAL 3004)	
Raw brushed	


Art. No. / EAN code	
	151S1279016 / 7330492008950
	151S1279005 / 7330492008943
	151S1272001 / 7330492008967
	151S1270002 / 7330492000787

Art. No. / EAN code	
	151S1309016 / 7330492008981
	151S1309005 / 7330492008974
	151S1302001 / 7330492008998
	151S1300002 / 7330492000794













w151 Extra large pendant s2



w151 Extra large pendant s3



Article-specific information

Version	s2	s3
Mounting	Ceiling suspended	Ceiling suspended
LED Colour temperature (CCT) / Luminous flux	2700 K / 4437 lm 3000 K / 4647 lm	2700 K / 5091 lm 3000 K / 5331 lm
Voltage / System power	220–240 V / 46 W	220–240 V / 46 W
Efficacy	100 lm / W	115 lm / W
Light control	DALI dim-Push dim	DALI dim-Push dim
Net weight	6.5 kg	11.5 kg
Packaging dimensions	L89 × W89 × H93 cm (0.74 m ³)	L142 × W142 × H54 cm (1.09 m ³)
Gross weight	15 kg	24 kg
2700 K Colour temperature (CCT)	Art. No. / EAN code	Art. No. / EAN code
Traffic White (RAL 9016) 	151S2279016 / 7330492009018	151S3279016 / 7330492009070
Jet black (RAL 9005) 	151S2279005 / 07330492009001	151S3279005 / 7330492009063
Red orange (RAL 2001) 		
Carmin red (RAL 3002) 	151S2273002 / 7330492009025	
Purple red (RAL 3004) 		151S3273004 / 7330492009087
Raw brushed 	151S2270002 / 7330492000800	151S3270002 / 7330492000824
3000 K Colour temperature (CCT)	Art. No. / EAN code	Art. No. / EAN code
Traffic white (RAL 9016) 	151S2309016 / 7330492009049	151S3309016 / 7330492009100
Jet black (RAL 9005) 	151S2309005 / 7330492009032	151S3309005 / 7330492009094
Red orange (RAL 2001) 		
Carmin red (RAL 3002) 	151S2303002 / 7330492009056	
Purple red (RAL 3004) 		151S3303004 / 7330492009117
Raw brushed 	151S2300002 / 7330492000817	151S3300002 / 7330492000831