




w225 lon 3000 K narrow



w225 lon 3000 K wide



w225 lon b4040



Technical information

Physical

Material	Lamp body & wall bracket: aluminium Base & pin: steel
-----------------	--

Optics	Glare shade: polyamide Lens: polycarbonate
---------------	---

IP rating	20
------------------	----

Protection class	III
-------------------------	-----

LED

Light source	COB LED (included)
---------------------	--------------------

Lifetime expectancy	L80 / 50,000 h
----------------------------	----------------

CRI Colour rendering index	97
-----------------------------------	----

Standard deviation of colour matching	3-step MacAdam
--	----------------

Replaceable by a professional

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wästberg Lighting AB apply.

Article-specific information

Version	b4040
Mounting	Base
LED Colour temperature (CCT) / Luminous flux	3000 K / 439 lm
Voltage / System power	100–240 V / 6.3 W
Efficacy	60 lm / W
Beam angle / Optics	Wide / Lens
Light control	Dimmable
Net weight	3.1 kg

2700 K Colour temperature (CCT)

Traffic white (RAL 9016)	<input type="radio"/>
Jet black (RAL 9005)	<input checked="" type="radio"/>
Raw tumbled	<input type="radio"/>

3000 K Colour temperature (CCT)

Traffic white (RAL 9016)	<input type="radio"/>
Jet black (RAL 9005)	<input checked="" type="radio"/>
Raw tumbled	<input type="radio"/>

Accessories

Adapter suitable for USM Haller Table

Adapter suitable for USM Haller Shelf

Adapter suitable for Vitra Joyn 2

Adapter suitable for Vitra Tyde 2

Narrow / Lens

Wide / Reflector & diffuser

Packaging dimensions

Art. No. / EAN code	

Art. No. / EAN code

Art. No. / EAN code

225B40400230W / 7330492000541
225B40400530W / 7330492000558
225B40402030W / 7330492001845

Art. No. / EAN code


225-N01

L64.8 x W31.6 x H10.1 cm (0.02 m³)

w225 lon p4040



w225 lon b9040



Article-specific information

Version	p4040	b9040
Mounting	Pin - integrated (hole \varnothing 14 mm)	Floor base
LED Colour temperature (CCT) / Luminous flux	3000 K / 439 lm	2700 K / 380 lm 3000 K / 405 lm
Voltage / System power	100–240 V / 6.3 W	100–240 V / 6.3 W
Efficacy	60 lm / W	70 lm / W
Beam angle / Optics	Wide / Lens	Narrow / Lens
Light control	Dimmable	Dimmable
Net weight	0.3 kg	3.2 kg

2700 K Colour temperature (CCT)

Traffic white (RAL 9016)	<input type="radio"/>
Jet black (RAL 9005)	<input checked="" type="radio"/>
Raw tumbled	<input type="radio"/>

Art. No. / EAN code

Art. No. / EAN code

225B90400227N / 7330492000602
225B90400527N / 7330492000619

3000 K Colour temperature (CCT)

Traffic white (RAL 9016)	<input type="radio"/>
Jet black (RAL 9005)	<input checked="" type="radio"/>
Raw tumbled	<input type="radio"/>

Art. No. / EAN code

225P40400230W / 7330492000565
225P40400530W / 7330492000572
225P40402030W / 7330492001852

Art. No. / EAN code

225B90400230N / 7330492000589
225B90400530N / 7330492000596

Accessories

Adapter suitable for USM Haller Table	
Adapter suitable for USM Haller Shelf	
Adapter suitable for Vitra Joyn 2	
Adapter suitable for Vitra Tyde 2	
Narrow / Lens	
Wide / Reflector & diffuser	
Packaging dimensions	


Art. No. / EAN code

225ACC001 / 7330492002002
225ACC006 / 7330492002019
225ACC002 / 7330492002026
225ACC003 / 7330492002033
225-N01

Art. No. / EAN code

225-W01

w225 lon br4040



w225 lon br0



Article-specific information

Version	br4040	br0
Mounting	Wall bracket	Wall bracket
LED Colour temperature (CCT) / Luminous flux	3000 K / 439 lm	2700 K / 380 lm 3000 K / 405 lm
Voltage / System power	100–240 V / 6.3 W	100–240 V / 6.3 W
Efficacy	60 lm / W	70 lm / W
Beam angle / Optics	Wide / Lens	Narrow / Lens
Light control	Dimmable	Dimmable
Net weight	0.4 kg	0.3 kg

2700 K Colour temperature (CCT)

Traffic white (RAL 9016)	<input type="radio"/>
Jet black (RAL 9005)	<input checked="" type="radio"/>
Raw tumbled	<input type="radio"/>

Art. No. / EAN code

Art. No. / EAN code

225BR00227N / 7330492000664
225BR00527N / 7330492000671
225BR02027N / 7330492001906

3000 K Colour temperature (CCT)

Traffic white (RAL 9016)	<input type="radio"/>
Jet black (RAL 9005)	<input checked="" type="radio"/>
Raw tumbled	<input type="radio"/>

Art. No. / EAN code

225BR40400230W / 7330492000626
225BR40400530W / 7330492000633
225BR40402030W / 7330492001883

Art. No. / EAN code

225BR00230N / 7330492000640
225BR00530N / 7330492000657
225BR02030N / 7330492001890

Accessories

Adapter suitable for USM Haller Table
Adapter suitable for USM Haller Shelf
Adapter suitable for Vitra Joyn 2
Adapter suitable for Vitra Tyde 2
Narrow / Lens
Wide / Reflector & diffuser

Art. No. / EAN code

225-N01

Art. No. / EAN code

225-W01