











AMIGO (Spanish for "friend") is the first joint project from this father and son team, who exemplify two generations of Spanish design. A central opaque disc holds a light source surrounded by a translucent, vertical shade, that diffuses luminosity and produces a glare-free halo of filtered light. Its airtight resistance protects the electrical fittings and also prevents insects from getting in, so that it stays clean and maintains an even glow.

The design was commissioned by Santa & Cole as part of the remodelling of our headquarters in Belloch; it repeatedly comes into sight on pergolas and passageways, walls and ceilings. The Amigo wall lamp is an exercise of impeccable simplicity, where nothing is superfluous.

### **General description:**

White metallic structure.
Cylindrical translucent methacrylate diffuser.
Suitable for outdoor use.
Suitable for Outlet Box (UL market).

## Approximate weight (unpacked):

2,4 Kg / 5 lb

### **Technical information:**

Light source included (dimmable): Strip of LEDs

Rated input wattage: 40 W Operating current: 700 mA Colour Temp.: 2.700 K

CRI: 90

Lifetime: 40.000 h Luminous flux: 708 lm

Built-in adjustable LED.


Suitable for dimming systems 1-10V. (External dimmer switch 1-10V not included). Energy efficiency class (E.E.C): A++...A.

Suitable for outdoor use. Always use this light source.

Input voltaje: 90 ~ 305 Vac.

(50 Hz / 60 Hz). According to destination.





# **Amigo**

Gonzalo Milá, Miguel Milá. 2009 Outdoor



# Regulations:

UNE-EN 60598 UNE-EN 55015

UNE-EN 60529

UNE-EN 62031

UNE-EN 61000-3-2

UNE-EN 61347-2-13

UL

WET locations

UL - 1598 UL - 8750

E - 336377

### Maintenance:

Clean with a smooth cloth. Do not use ammonia, solvents or abrasive cleaning products.

### Others:

The lamp is delivered in one package.

The assembly instructions are delivered with the product.

### Model:

