AIRMOD


88200087 AIRMOD MONO S 900-927 RB GR-S Suspension light with rose






Description

AIRMOD MONO suspension light with surface-mounted power supply box (Stefan Diez design). SILVER finishing. Equipped with an interchangeable perforated collimator GRID, SILVER finishing. Low-voltage head, diameter 100, can swivel through 360° thanks to a nickel-plated copper double hoop. Silver anodised aluminium fin passive heat sink. Interchangeable perforated tubular collimator in silver anodised aluminium



Light specifications and controlling

- CoB LED Module 900 lm (without endcap), IRC>90, 2700 K, 3 SDCM
- $\bullet\,$ Interchangeable optics unit composed of a mixing chamber and a Wide Beam 50° glass lens
- Driver with constant current output, dimmable by Bluetooth Casambi



Installation and maintenance

- Dimensions: Head: Ø100x160 mm, Box: Ø113x60 mm
- Box in anodised aluminium containing a 220-240 V 50/60 Hz power supply and a 3 x 2.5 mm² terminal block
- For surface mounting via 2 x M3 screws with centre distance 96 mm (not supplied).
- Suspension wires adjustable in height, up to 3 m.











Characteristics

• Warranty: 5 years

• 50 000 h L80/B10 at 25°C

• Operating temperature: -5 °C to +35 °C

Protection: IP20Electrical class: Class I

• Power consumption: 12 W

Photobiological hazard: Group 1

• Fire resistance: 850 °C

Weight: 1,17 kg

• Designed and made in France and Germany