

# SPHERE I

3.8W | 220 lm | 2000-2800K

SPHR-G50-4W-2000-2800K-E14-MP

Sphere Small 4W WoD 2000K to 2800K E14 Matte Porcelain UK/EU LED Bulb


tala.

Tala's Sphere I light bulb is a refined and effective light source. Boasting Dim to Warm and flicker-free behaviour, Sphere I can dim from a cool, bright light, to its lowest setting while maintaining a warm, amber glow. Fitted with an E14 base cap, this is a stylish solution for any number of table, floor or ceiling lights.




## PHYSICAL

Bulb diameter:	50mm
Bulb length:	82mm
Glass shape:	G50
Base:	E14
Materials:	Glass & nickel
Glass finish:	Matte White
Weight:	18g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54



— CIE180  
— CIE120

IES/LDT photometry files  
and product photography  
available on request



## ELECTRICAL

Power:	3.8W
Current:	0.02A
Voltage:	220-240V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	58 lm/W
Lifetime:	15,000 hrs

## ILLUMINATION

CCT:	2000-2800K
Lumens:	220 lm
Incandescent equiv.:	22W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	80
TM30 - Rg	101
TM30 - Rf	94



## DIMMING

Dimmable 0-100%  
Recommended dimmer: Varilight V-Pro  
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,  
London, E2 9DG, United Kingdom

Tala Europe B.V. Bertus Aafjeshove 40  
Nieuwegein 3437 JN

## LOGISTICAL

Unit Packaging	Outer Carton
PC/Ctn: 1	PC/Ctn: 10
Gross weight: 30	Gross weight: 0.32
L 55 x W 55 x H 80mm	L 635 x W 108 x H 62cm

tala.co.uk | hello@tala.co.uk | +44 7700 170343

Specification subject to change without  
notice. Refer to our website for the most  
recent product documentation. Tala  
designs in the EU/UK are protected by  
registered and or unregistered design rights

## WARRANTY

2 years

## EAN

5060400152902