

TOMOSHI PORTABLE LAMP

Tomoshi Portable Lamp - 5744171287

This portable table lamp emits a soft, glare-free light, that illuminates the surface below and provides some ambient light. The replaceable LED light source is contained towards the base of the design. With a minimalistic expression and quality materials, it is designed with longevity and usability in mind.



nendo

In 2002 Oki Sato founded nendo design studio. nendo means 'clay' in Japanese – or more specifically, modelling clay such as plasticine. A unique material that makes it easy to do creative modelling.



Product info

Information

Please note that Tomoshi Portable comes with a USB-C cable but without adapter. Separate USB adapter is available as accessory. Compatible with standard USB adapters (Min 1.5A)

Mounting

Cable length: 1 m. USB-C to USB-A cable. Battery: rechargeable and replaceable 1 x 6200mAh White light indicator on base when charging. Light control: Switch on body. Stepless and step dimming function. Battery lifetime: 5.5hours at 100%, 48 at 5.5%. Function to set a fixed light level. Lumen: 210 lm at 100%. Dim to Warm, LED 2000K – 2700K 3W.

Finish

White or Dark Brown, matt painted.

Materials

Strap: Retractable strap in Genuine Leather. Body: Recycled Polymer. Diffuser: Polymer

Sizes and weights

width x Height x Length (mm) | 125 x 241 x 125 Max 0.7 kg

Class


IP21, suited for indoor use.

Information

Please note that Tomoshi Portable comes with a USB-C cable but without adapter. Separate USB adapter is available as accessory. Compatible with standard USB adapters (Min 1.5A)




Related products



Panthella 250 Portable Lamp



PH 2/1 Portable Lamp



Panthella 160 Portable Lamp
Anniversary Edition

Spare parts & accessories

Product	Variant number
Tomoshi Portable Light Brown leather strap	5744171300
Tomoshi Portable Dark Brown leather strap	5744171313
Tomoshi Portable rep. kit battery	5744171326
Tomoshi Portable rep. kit PCB	5744171339
Tomoshi Portable rep. kit D2W board	5744171342

Data specifications

Colour	White	Length	125
Width	125	Height	241
Built-in Height	-	IP class	-
Class	III	Net Weight	0.7
Standby (W)	-	Power Factor (P = 100 % / P = 50 %)	-
Inrush Current	-	Light source	-
Kelvin	2700	CRI	95
SDCM	3	Lumen	-
Watt	-	Efficacy	-
Light control	-	Min. Dim Level (%)	-
UGR Transversal / Axial	-	L80B50 (hours)	>50.000
Driver life	-		