

VL 56 PENDANT

VL 56 Pendant - 5741113099

The pendant emits downward directed glare-free light. The radial perforation pattern around the opening creates a softer transition between light and darkness. The perforations create a soft beautiful pattern of light both on the shade and on the surrounding surfaces.



Vilhelm Lauritzen

Vilhelm Lauritzen (1894–1984) is one of the most significant architects in the history of Denmark; he was the trail-blazing figurehead of Danish functionalism. A number of his buildings – Nørrebro Theatre (1931–32), Daells Varehus department store (1928–35), Radihuset (1936–41) and the first airport built in Kastrup (1937–39) – represented the concentrated essence of contemporary life.



Product info

Information

Please note that the brass surfaces are untreated. This means that the surface will change over time and develop a patina.

Mounting

E27, white textile cable 2x0.75 mm². Canopy: Yes. Cable length: 4 m.

Finish

Polished brass or chrome. Wet painted white inner side.

Materials

Shade, tub and lid in polished untreated brass or chrome plated aluminium.

Sizes and weights

Width x Height x Length (mm) | 177 x 112 x 177 Max 1.6 kg

Class

Ingress protection IP20. Electric shock protection II w/o ground.

Information

Please note that the brass surfaces are untreated. This means that the surface will change over time and develop a patina.



Light distribution diagrams

Cartesian | solux | Polar

Data specifications

Colour	High lustre chrome plated	Length	177
Width	177	Height	112
Built-in Height	-	IP class	20
Class	II	Net Weight	1.6
Standby (W)	-	Power Factor (P = 100 % / P = 50 %)	-
Inrush Current	-	Light source	-
Kelvin	-	CRI	-
SDCM	-	Lumen	-
Watt	-	Efficacy	-
Light control	-	Min. Dim Level (%)	-
UGR Transversal / Axial	24.2/23.9	L80B50 (hours)	-
Driver life	-		