




PROJECT

TYPE


NOTES

QUANTITY

DATE



Round ceiling recessed downlight made from die-cast aluminium; adjustable; surface Black Matt; powder coated, matt texture; RAL 9011; inner ring black; installation without tools using wire springs; suitable for ceiling thickness of 4-25 mm; recessed depth 75 mm; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; 350° rotatable and 60° tiltable; degree of protection IP20; Class 2; IC rated; lamp not included;



LUMINAIRE

Ceiling
Semi-Recessed
tilt max 60 °
rotation 350 °
Black Matt
RAL 9011 ^a
IP20
IC rated
Interior

LAMP

lamp PAR16
socket GU10
max. per socket 12.0 W
CRI ≥ 90

Optical

UGR ≤ 19

Electrical

100 - 240 V
Class II
Standard

Physical

diameter 135 mm
height 61 mm
0.42 kg
wire springs

Cutout

diameter 127 mm
min. ceiling thickness 4 mm
max. ceiling thickness 25 mm
recessed depth 75 mm



^a Colour may deviate slightly due to production conditions

MEASURED LAMPS

PAR16 LAMP 2700K CRI90
465 lm

PAR16 LAMP 3000K CRI90
485 lm

LIGHT DISTRIBUTION



**ELECTRICAL ACCESSORIES****LED LAMPS**

Type	Colour	Voltage	Item number
	Black Texture		W901228B3
	Black Texture		W901228B5

LAMPS**PAR16 LED Lamp**

Type	Colour	Voltage	Ø·H (MM)	Item number
2700K >90 CRI GU10	White		50-60	901228W3
3000K >90 CRI GU10	White		50-60	901228W5
2700K >80 CRI GU10	Silver		50-55	905227S2
3000K >80 CRI GU10	Silver		50-55	905227S4