




PROJECT

TYPE


NOTES

QUANTITY

DATE



Round ceiling recessed downlight made from die-cast aluminium; adjustable; surface White Matt; powder coated, matt texture; RAL 9010; inner ring black; installation without tools using blade springs; suitable for ceiling thickness of min. 4 mm; recessed depth 75 mm; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; 350° rotatable and 60° tiltable; degree of protection IP20; Class 2; IC rated; lamp not included;



LUMINAIRE

Ceiling
Semi-Recessed
tilt max 60 °
rotation 350 °
White Matt
RAL 9010 ^a
IP20
IC rated
Interior

LAMP

lamp PAR16
socket GU10
max. per socket 12.0 W
CRI ≥ 90

Optical

UGR ≤ 19

Electrical

100 - 240 V
Class II
Standard

Physical

diameter 135 mm
height 61 mm
0.42 kg
blade springs

Cutout

diameter 127 mm
min. ceiling thickness 4 mm
recessed depth 75 mm



^a Colour may deviate slightly due to production conditions

MEASURED LAMPS

PAR16 LAMP 3000K CRI90
540 lm

PAR16 LAMP 2700K CRI90
530 lm

LIGHT DISTRIBUTION





ELECTRICAL ACCESSORIES

LED LAMPS

Type	Colour	Voltage	Item number
	Black Texture		W901228B3
	Black Texture		W901228B5

LAMPS

PAR16 LED Lamp

Type	Colour	Voltage	Ø·H (MM)	Item number
2700K >90 CRI GU10	White		50-60	901228W3
3000K >90 CRI GU10	White		50-60	901228W5
2700K >80 CRI GU10	Silver		50-55	905227S2
3000K >80 CRI GU10	Silver		50-55	905227S4