



PROJECT

TYPE


NOTES

QUANTITY

DATE



Rectangular ceiling surface mounted downlight made from die-cast aluminium; rounded edges; surface Gold Brushed; No matching RAL; lamp socket GU10; lamp type PAR16; 2x max. 12W; 100 - 240 V; degree of protection IP20; Class I; UGR ≤ 19; lamp not included; optional single inner cover available;



LUMINAIRE

Ceiling
Surface
Gold Brushed
No matching RAL
IP20
Interior

LAMP

lamp 2 x PAR16
socket GU10
max. per socket 12.0 W
CRI ≥ 80 / 90 / 90

Optical

UGR ≤ 19

Electrical

100 - 240 V
Class I
Standard

Physical

length 174 mm
width 90 mm
height 90 mm
1.01 kg




MEASURED LAMPS

PAR16 LAMP 2700K CRI90
925 lm

PAR16 LAMP 3000K CRI90
965 lm

PAR16 LAMP 2700K CRI80
770 lm

LIGHT DISTRIBUTION





ELECTRICAL ACCESSORIES

LED LAMPS

Type	Colour	Voltage	Item number
	Black Texture		W901228B3
	Black Texture		W901228B5

LAMPS

PAR16 LED Lamp

Type	Colour	Voltage	Ø·H (MM)	Item number
2700K >90 CRI GU10	White		50-60	901228W3
3000K >90 CRI GU10	White		50-60	901228W5
2700K >80 CRI GU10	Silver		50-55	905227S2
3000K >80 CRI GU10	Silver		50-55	905227S4

OPTICAL ACCESSORIES

Single Inner Cover

Type	Colour	Voltage	L·W·H (MM)	Item number
DOCUS max. 10W	Black		62-62-39.5	911021B1
DOCUS max. 10W	Gold		62-62-39.5	911021G1
DOCUS max. 10W	White		62-62-39.5	911021W1