



PROJECT

TYPE


NOTES

QUANTITY

DATE



Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface Aluminium Brushed; RAL 9006; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP20; Class 1; UGR ≤ 16; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; lamp not included; optional single inner cover available;



LUMINAIRE

Ceiling
Surface
Aluminium Brushed
RAL 9006 ^a
IP20
Interior

LAMP

lamp PAR16
socket GU10
max. per socket 12.0 W
CRI ≥ 80 / 90 / 90

Optical

UGR ≤ 16
≥65° < 1500 cd/m²

Electrical

100 - 240 V
Class I
Standard

Physical

diameter 114 mm
height 100 mm
0.61 kg

^a Colour may deviate slightly due to production conditions




MEASURED LAMPS

PAR16 LAMP 2700K CRI80
385 lm

PAR16 LAMP 2700K CRI90
465 lm

PAR16 LAMP 3000K CRI90
485 lm

LIGHT DISTRIBUTION



**ELECTRICAL ACCESSORIES****LED LAMPS**

Type	Colour	Voltage	Item number
	Black Texture		W901228B3
	Black Texture		W901228B5

LAMPS**PAR16 LED Lamp**

Type	Colour	Voltage	Ø·H (MM)	Item number
2700K >90 CRI GU10	White		50-60	901228W3
3000K >90 CRI GU10	White		50-60	901228W5
2700K >80 CRI GU10	Silver		50-55	905227S2
3000K >80 CRI GU10	Silver		50-55	905227S4

OPTICAL ACCESSORIES**Single Inner Cover**

Type	Colour	Voltage	Ø·H (MM)	Item number
RAY max. 10W	Black		67-54	911041B1
RAY max. 10W	Gold		67-54	911041G1
RAY max. 10W	Champagne		67-54	911041M1
RAY max. 10W	White		67-54	911041W1