



PROJECT

TYPE


NOTES

QUANTITY

DATE



Ceiling surface spotlight made from die-cast aluminium; with rectangular base; surface Bronze; wet painted, matt smooth; RAL 7013; inner ring black; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; CRI $\geq$ 90; beam angle 31°; 220 - 240 V; 350° rotatable and 90° tiltable; degree of protection IP20; Class I; driver included; optional honeycomb louver available, to reduce glare; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



LUMINAIRE

Ceiling
Surface
tilt max 90 °
rotation 350 °
Bronze
RAL 7013 ^a
IP20
Interior
2890 lm

LED Module

2700 K
CRI $\geq$ 90
L70 / 55000h
 $\leq$ 2 SDCM (initial MacAdam)
480 lm
72 lm/W ^b

Optical

Medium (standard)
beam angle 31°
CIE flux code: 99 100 100 100
100

Electrical

phase-cut dim
220 - 240 V
system 40 W
Class I
Standard


Physical

diameter 35 mm
height 55 mm
1.34 kg

^a Colour may deviate slightly due to production conditions

^b Without electrical and optical losses

LIGHT DISTRIBUTION





CONE DIAGRAM

medium (standard) 31°

h (m)	E0° (lx)	ø (m)
1	1390	0.55
2	350	1.10
3	150	1.65
4	90	2.21
5	60	2.76

OPTICAL ACCESSORIES

Honeycomb Louver

Type	Colour	Voltage	Ø (MM)	Item number
BLIEK petit CENO LECA PIRRO QITO 1.0	Black		29	915230B0