



PROJECT

TYPE

NOTES

QUANTITY

DATE



Ceiling surface spotlight made from die-cast aluminium; with rectangular base; surface Bronze; wet painted, matt smooth; RAL 7013; inner ring black; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; ≤ 2 SDCM (initial MacAdam); CRI ≥ 90 ; beam angle 31°; 220 - 240 V; 350° rotatable and 90° tiltable; degree of protection IP20; Class I; driver included; optional honeycomb louver available, to reduce glare; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

LUMINAIRE

Ceiling
Surface
tilt max 90 °
rotation 350 °
Bronze
RAL 7013 ^a
IP20
Interior
540 lm


LED Module

3000 K
CRI ≥ 90
L70 / 55000h
 ≤ 2 SDCM (initial MacAdam)

Optical

Medium (standard)
beam angle 31°
CIE flux code: 99 100 100 100 100

LIGHT DISTRIBUTION




Electrical

phase-cut dim
220 - 240 V
system 8.8 W
Class I
Standard

Physical

diameter 35 mm
height 55 mm
0.21 kg

^a Colour may deviate slightly due to production conditions





CONE DIAGRAM

medium (standard) 31°

h (m)	EO° (lx)	ø (m)
1	1550	0.56
2	390	1.12
3	170	1.68
4	100	2.23
5	60	2.79

OPTICAL ACCESSORIES

Honeycomb Louver

Type	Colour	Voltage	Ø (MM)	Item number
BLIEK petit CENO LECA PIRRO QITO 1.0	Black		29	915230B0