



PROJECT

TYPE


NOTES

QUANTITY

DATE



Squared ceiling surface mounted downlight made from die-cast aluminium; surface White Matt; powder coated; matt texture; RAL 9010; with COB (Chip on Board) technology for maximum efficiency; DALI dim; light colour 2700 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; Class I; UGR ≤ 13 ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above $65^\circ \leq 1500 \text{ cd/m}^2$; optional single inner reflector and single inner cover available; light source replaceable by Wever & Ducreé or by a professional with explicit authorization;



LUMINAIRE

Ceiling
Surface
White Matt
RAL 9010 ^a
IP20
Interior
600 lm

LED Module

2700 K
CRI ≥ 90
L70 / 50000h
 ≤ 3 SDCM (initial MacAdam)
730 lm
91 lm/W ^b

Optical

Medium (standard)
beam angle 21°
UGR ≤ 13
CIE flux code: 93 99 100 100
100
 $\geq 65^\circ < 1500 \text{ cd/m}^2$

Electrical


DALI
220 - 240 V
system 8.1 W
Class I
Standard

Physical

length 100 mm
width 100 mm
height 100 mm
0.74 kg

^a Colour may deviate slightly due to production conditions
^b Without electrical and optical losses

LIGHT DISTRIBUTION





Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0	0	0	0	0
LSF	1	1	1	1	1

MF LMF × RSMF × LLMF × LSF

MF Maintenance Factor

LMF^a Luminaire Maintenance Factor

RSMF^a Room Surface Maintenance Factor

LLMF Lamp Lumens Maintenance Factor

LSF Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

OPTICAL ACCESSORIES

Single Inner Cover

Type	Colour	Voltage	L·W·H (MM)	Item number
BOX max. 10W	Black		62·62·49	911011B1
BOX max. 10W	Gold		62·62·49	911011G1
BOX max. 10W	Champagne		62·62·49	911011M1
BOX max. 10W	White		62·62·49	911011W1

Single Inner Reflector

Type	Colour	Voltage	L·W·H (MM)	Item number
BOX max. 10W	Black		93.5·93.5·50.5	911211B1
BOX max. 10W	Gold		93.5·93.5·50.5	911211G1
BOX max. 10W	Champagne		93.5·93.5·50.5	911211M1
BOX max. 10W	White		93.5·93.5·50.5	911211W1