



PROJECT

TYPE


NOTES

QUANTITY

DATE



Rectangular ceiling surface mounted downlight made from die-cast aluminium; surface Aluminium Brushed; RAL 9006; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2000 - 3000 K colour warm dimming; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; Class I; UGR ≤ 13 ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above $65^\circ \leq 1500 \text{ cd/m}^2$; optional double inner reflector and single inner cover available; light source replaceable by Wever & Ducre or by a professional with explicit authorization; control gear replaceable by end-user;



LUMINAIRE

Ceiling
Surface
Aluminium Brushed
RAL 9006 ^a
IP20
Interior
820 lm

LED Module

colour warm dimming
2000 - 3000 K
CRI ≥ 90
L70 / 50000h
 ≤ 3 SDCM (initial MacAdam)
1090 lm
90 lm/W ^b

Optical

Medium (standard)
beam angle 21°
UGR ≤ 13
CIE flux code: 94 100 100 100
 $\geq 65^\circ < 1500 \text{ cd/m}^2$


Electrical

phase-cut dim
220 - 240 V
system 14.3 W
Class I
Standard

Physical

length 188 mm
width 100 mm
height 100 mm
1.08 kg

LIGHT DISTRIBUTION



^a Colour may deviate slightly due to production conditions

^b Without electrical and optical losses



Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.95	0.91	0.86	0.82	0.77
LSF	1	1	1	1	1

MF LMF × RSMF × LLMF × LSF

MF Maintenance Factor

LMF^a Luminaire Maintenance Factor

RSMF^a Room Surface Maintenance Factor

LLMF Lamp Lumens Maintenance Factor

LSF Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

OPTICAL ACCESSORIES

Double Inner Reflector

Type	Colour	Voltage	L·W·H (MM)	Item number
BOX 2.0 max. 10W	Black		181-93-50	911251B1
BOX 2.0 max. 10W	Gold		181-93-50	911251G1
BOX 2.0 max. 10W	Champagne		181-93-50	911251M1
BOX 2.0 max. 10W	White		181-93-50	911251W1

Single Inner Cover

Type	Colour	Voltage	L·W·H (MM)	Item number
BOX max. 10W	Black		62-62-49	911011B1
BOX max. 10W	Gold		62-62-49	911011G1
BOX max. 10W	Champagne		62-62-49	911011M1
BOX max. 10W	White		62-62-49	911011W1