




PROJECT

TYPE


NOTES

QUANTITY

DATE



Rectangular ceiling surface mounted downlight made from die-cast aluminium; rounded edges; with 2 spotlights; adjustable; surface Aluminium Brushed; RAL 9006; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; CRI ≥ 90 ; beam angle 31°; spotlight heads 350° rotatable and 35° tiltable; degree of protection IP20; Class I; driver included; optional honeycomb louver available, to reduce glare;



LUMINAIRE

Ceiling
Surface
tilt max 35 °
rotation 350 °
Aluminium Brushed
RAL 9006 ^a
IP20
Interior
420 lm

LED Module

2700 K
CRI ≥ 90
L80 / 50000h
 ≤ 2 SDCM (initial MacAdam)

Optical

beam angle 31°

Electrical

phase-cut dim
220 - 240 V
system 11.0 W
Class I
Standard

Physical

length 184 mm
width 80 mm
height 46 mm
0.6 kg
surface

^a Colour may deviate slightly due to production conditions

198664L3



OPTICAL ACCESSORIES

Honeycomb Louver

Type	Colour	Voltage	Ø (MM)	Item number
BLIEK petit CENO LECA PIRRO QITO 1.0	Black		29	915230B0