




PROJECT

TYPE


NOTES

QUANTITY

DATE



Rectangular ceiling surface mounted downlight made from die-cast aluminium; rounded edges; with 2 spotlights; adjustable; surface White Matt; powder coated; matt texture; No matching RAL; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; CRI ≥ 90 ; beam angle 31°; spotlight heads 350° rotatable and 35° tiltable; degree of protection IP20; Class I; driver included; optional honeycomb louver available, to reduce glare;



LUMINAIRE

Ceiling
Surface
tilt max 35 °
rotation 350 °
White Matt
No matching RAL
IP20
Interior
420 lm

LED Module

2700 K
CRI ≥ 90
L80 / 50000h
 ≤ 2 SDCM (initial MacAdam)

Optical

beam angle 31°

Electrical

phase-cut dim
220 - 240 V
system 11.0 W
Class I
Standard

Physical

length 184 mm
width 80 mm
height 46 mm
0.6 kg
surface

198664W3



OPTICAL ACCESSORIES

Honeycomb Louver

Type

BLIEK petit | CENO | LECA | PIRRO | QITO 1.0

Colour

Black

Voltage

Ø (MM)

29

Item number

915230B0