



PROJECT

TYPE

NOTES

QUANTITY

DATE



Suspended luminaire in an elongated capsule shape made from opal polyethylene; rounded end caps made from aluminium in black; suspended vertically or horizontally; No matching RAL; inclusive cable suspension max. 2500 mm; light colour: tunable white diodes (2700-5000 K); CRI ≥ 90 ; PCB; 220 - 240 V; degree of protection IP20; Class I; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

LUMINAIRE

Ceiling
Suspended
Opal White + Black
No matching RAL
IP20
Interior
3000 lm

LED Module

tunable white
2700 - 5000 K
CRI ≥ 90
 ≤ 3 SDCM (initial MacAdam)

Optical


Opal

Electrical

DALI-2 DT8
220 - 240 V
system 28.0 W
Class I
Standard

Physical

Black ceiling base
diameter 200 mm
height 1022 mm
2.9 kg
cable length max. 2500 mm



**SUSPENSION****Power Cable
Type****Colour**
Black**Voltage****Length (MM)**
6000**Item number**
913240B0**Steel Suspension Cable
Type****Colour**
Black**Voltage****Length (MM)**
6000**Item number**
913230B0