



PROJECT

TYPE


NOTES

QUANTITY

DATE



Squared ceiling surface mounted downlight made from die-cast aluminium; surface Champagne Brushed; No matching RAL; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP20; Class I; optional inner reflector available; lamp not included;



LUMINAIRE

Ceiling
Surface
Champagne Brushed
No matching RAL
IP20
Interior

LAMP

lamp PAR16
socket GU10
max. per socket 12.0 W
CRI ≥ 80 / 90 / 90

Optical

UGR ≤ 19

Electrical

100 - 240 V
Class I
Standard

Physical

length 70 mm
width 70 mm
height 82 mm
0.16 kg




MEASURED LAMPS

PAR16 LAMP 3000K CRI90
450 lm

PAR16 LAMP 2700K CRI90
430 lm

PAR16 LAMP 2700K CRI80
360 lm

LIGHT DISTRIBUTION





OPTICAL ACCESSORIES

Inner Reflector

Type	Colour	Voltage	Item number
BOX mini max. 10W	Black		900199B1
BOX mini max. 10W	Gold		900199G1
BOX mini max. 10W	Champagne		900199M1
BOX mini max. 10W	Bronze		900199Q1
BOX mini max. 10W	White		900199W1

ELECTRICAL ACCESSORIES

LED LAMPS

Type	Colour	Voltage	Item number
	Black Texture		W901228B3
	Black Texture		W901228B5

LAMPS

PAR16 LED Lamp

Type	Colour	Voltage	Ø·H (MM)	Item number
2700K >90 CRI GU10	White		50-60	901228W3
3000K >90 CRI GU10	White		50-60	901228W5
2700K >80 CRI GU10	Silver		50-55	905227S2
3000K >80 CRI GU10	Silver		50-55	905227S4