
# Piroscafo Rust

## Ernesto Gismondi



**IP**65 (≟)



#### LUMINAIRE

- Watt: **14W** 

– Delivered lumen output: **1143lm** 

– CCT: **3000K**– Efficiency: **77%** 

Efficacy: 81.64lm/W

- CRI: **90** 

### **DESCRIPTION**

Lighting appliance for ground fixing with radial bidirectional light emission, using monochrome LED light sources. The appliance is made up of a body and a fixing base of EN-AB 47100 die-cast aluminium finished with a 3-stage outdoor treatment: nanotechnologies, anti-oxidizing primer, polyester painting. Equipped with a furukawa reflector Shiny shockresistant anti-UV polycarbonate screen AISI 316 fixing screws and silicon seals. Sealing degree IP65. Class IProvided with cable and IP67 connector for connection to the mains. Supports cables with 7 to 12 mm diameters. Technical specifications comply with the EN60598-1 norm. CE registration

#### **FEATURES**

- Product Code: **T081910** 

Colour: RustInstallation: Floor

- Material: **Aluminum, tempered glass** 

Series: Architectural Outdoordesign by: Ernesto Gismondi

#### **DIMENSIONS**

Length: 198 mm
Width: 170 mm
Height: 275 mm
Diameter: 190 mm

#### **SOURCES INCLUDED**

Category: LedNumber: 1Watt: 14W

- Color temperature (K): 3000K

