
Pin T Asimmetrico

LL1251042

Lombardo.





Technical information:


Installation:	Wall recess
Material:	Aluminium
Treatment:	Sea Treatment
Diffuser type:	Serigraphed glass
Lamp type:	LED
Energy performance class:	F
Colour temperature:	2700K
CRI:	>80
LB Factor:	L70B20 - 50.000h
Photobiological risk:	RG0
Power consumption (Watt):	2
Lumen:	200
Real Lumen:	67
Power supply:	integrated
LED:	AC DIRECT
Version with:	Kit
Insulation class:	CL.I
Power cable:	0.20 metri H05RN-F
Type of protection:	**IP 66**
Resistance to breakage:	**IK 07 2J xx5**
Standards and Marks of Conformity:	CE UKCA

Deflector made of aluminum. Codes LL12510: Kit consisting of Pin T Asimmetrico+ recess box 502 LB1250001.

Lombardo S.r.l.
Via Pizzigoni 3, Villongo (BG) - 24060 - Italy - **T** 0039 035 939 411 - **E** info@lombardo.it

Pin T Asimmetrico

LL1251042




Lombardo S.r.l.
Via Pizzigoni 3, Villongo (BG) - 24060 - Italy - **T** 0039 035 939 411 - **E** info@lombardo.it

Pin T Asimmetrico


LL1251042

Lighting simulation:



pin_t_asimm

Photometric curves:



Lombardo S.r.l.
Via Pizzigoni 3, Villongo (BG) - 24060 - Italy - **T** 0039 035 939 411 - **E** info@lombardo.it