


# Ago Bollard H300 2L

LL126323N

**Lombardo.**

## Technical information:

|                                    |                          |
|------------------------------------|--------------------------|
| Installation:                      | Ground                   |
| Material:                          | Aluminium                |
| Finish:                            | Brown Anodized Aluminium |
| Treatment:                         | Anodization              |
| Diffuser type:                     | Polycarbonate            |
| Lamp type:                         | LED                      |
| Energy performance class:          | F                        |
| Colour temperature:                | 4000K                    |
| CRI:                               | >80                      |
| LB Factor:                         | L80B50 - 50.000h         |
| Photobiological risk:              | RG1                      |
| Power consumption (Watt):          | 10                       |
| Lumen:                             | 1100                     |
| Real Lumen:                        | 540                      |
| Power supply:                      | ✓ integrated             |
| LED:                               | AC DIRECT                |
| Insulation class:                  | ⊕ CL.I                   |
| Type of protection:                | <b>IP 66</b>             |
| Resistance to breakage:            | <b>IK 07 2J xx5</b>      |
| Standards and Marks of Conformity: | CE UK CA                 |
| Dimming                            | Phase cut                |



# Ago Bollard H300 2L

LL126323N

**Lombardo.**



## Installation images:




# Ago Bollard H300 2L

LL126323N

**Lombardo.**

## Lighting simulation:



ago\_bollard\_300\_2l