


Tape 140

LL14522K1


Lombardo.



Technical information:

Installation:	Wall
Material:	Aluminium
Finish:	Corten
Treatment:	Sea Treatment
Diffuser type:	Frosted glass
Lamp type:	LED
Energy performance class:	E
Colour temperature:	2200K
CRI:	>90
LB Factor:	L80B20 - 50.000h
Photobiological risk:	RG0
Power consumption (Watt):	4
Lumen:	590
Real Lumen:	419
Power supply:	✓ included remotely
LED:	24V REMOTE
Version with:	 Kit
	DRIVER IP67 + BOX
Insulation class:	 CL.III
Type of protection:	IP 66
Resistance to breakage:	IK 06 1J xx3
Standards and Marks of Conformity:	 


Codes LL14512: Kit consisting of Tape 140 + LB1070068 (driver IP66) Codes LL14522: Kit consisting of Tape 140 + recess box 503 LB11660 + LB1070068 (driver IP66)



Tape 140

LL14522K1

Lombardo.



Installation images:




Lombardo S.r.l.

Via Pizzigoni 3, Villongo (BG) - 24060 - Italy - T 0039 035 939 411 - E info@lombardo.it

lombardo.it

Lighting simulation:



tape_140

Photometric curves:

