

DELTALIGHT



SPY II 39 TRIMLESS SOFT CRI90 3000K-1800K 35° EX PS

REFERENCE 12306722EP00-90D2W1-0404-0
SHORT REFERENCE 1123KD7V1NSS0





Selected finishes per part



BODY
Black (04)



TUBE
Black (04)

View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø kit
RECESSED DEPTH (MM)	65
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.2
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	Excl. LED power supply 350mA

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	35°
LED TECHNICS (LIGHT SOURCE)	623lm // 6W // 105lm/W
LED TECHNICS (LUMINAIRE)	477lm // 6,9W // 69lm/W

Requirements

MOUNTING KIT R53 TRIMLESS O.F.A.
LED POWER SUPPLY 350mA

DELTALIGHT

SPY II 39 TRIMLESS SOFT CRI90 3000K-1800K 35° EX PS

12306722EP00-90D2W1-0404-0

Accessories

SOFTENING LENS 39
SANDBLASTED LENS 39
LINEAR SPREAD LENS 39
HONEYCOMB 39

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 **Plasterboard**	32210 0050 - MOUNTING KIT R53 TRIMLESS O.F.A.	Required
 **Concrete + plaster**	32210 0050 - MOUNTING KIT R53 TRIMLESS O.F.A.	Required


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 — 1 -> 4 (4)

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 82



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 — 2 -> 6 (6)

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 84



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 — 1 -> 2 (2)

Dimtype: 1-10V or push button


Cutout dimension (mm): 55



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 — 1 -> 2 (2)

Dimtype: DALI

Cutout dimension (mm): 55



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL — 1 -> 3


Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54

DELTALIGHT

SPY II 39 TRIMLESS SOFT CRI90 3000K-1800K 35° EX PS


12306722EP00-90D2W1-0404-0



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 — 1 -> 2

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 48



21012 0368 LED POWER SUPPLY 120V - 350mA-DC / 7,7W DIM8 — 1 -> 1(1)

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 40



21012 0398 LED POWER SUPPLY 120V - 350mA-DC / 16W DIM8 — 2 -> 2(2)

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 55



21012 0515 LED POWER SUPPLY MULTI POWER DIM5 — 1 -> 1 (1)

Dimtype: DALI

Cutout dimension (mm): 55




21012 0615 LED POWER SUPPLY 350mA-DC 10W DIM5 — 1 -> 2

Dimtype: DALI

Cutout dimension (mm): 35

Mounting kits



32210 0050 MOUNTING KIT R53 TRIMLESS O.F.A.

Cutout dimension (mm): 82

Light altering devices

32210 0210 SOFTENING LENS 39

32210 0220 SANDBLASTED LENS 39

DELTALIGHT

SPY II 39 TRIMLESS SOFT CRI90 3000K-1800K 35° EX PS

12306722EP00-90D2W1-0404-0

32210 0230 LINEAR SPREAD LENS 39 ☐



32210 0240 HONEYCOMB 39 ☐

Notes: