

Product Code 00-6671-05-F1 Installation Instructions 3D File Photometry Dialux | ULD Revit (BIM)



Alive Single with glass difusor

Francesc Vilaró

Pendant Alive Single with glass difusor LED 8.5 LED warm-white 2700K ON-OFF Black 454lm

Technical features

Luminaire total power: 8.5W

Real lumens: 454 Real Im/W: 53

Correlated Colour Temperature (CCT): LED warm-white 2700K

Lens / reflector angle: FLOOD 75°

UGR: <=16

Structure material: Aluminium, Steel

Structure finish: Black

Diffuser material: Methacrylate, Glass Diffuser finish: Tinted, Transparent Voltage / frequency: 100-277V/50-60Hz

Dimming protocol: ON-OFF

Power Factor: 0.90

THD%: 20

Useful life: 50,000h L80B20

Warranty: 5 years











Luminotechnic features

Luminance C0°G65°: 938 Luminance C90°G65°: 975

CRI: 80

MacAdam steps: 2

Photobiological risk: RG1

UGR		
S=0.250		
Ceiling / cavity	0.7	
Walls	0.5	
Working Plane	0.2	
Room dimensions	X=4H, Y=8H	
UGR crosswise	14.1	
UGR lengthwise	14.1	

Lampholder	Quantity	Light source power (W)	Correlated Colour Temperature (CCT)
LED	1	6.9W	LED warm- white 2700K






Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.



Product Code 00-6671-05-F1

Installation Instructions 3D File Photometry Dialux | ULD Revit (BIM)



Alive Single with glass difusor

Francesc Vilaró

Pendant Alive Single with glass difusor LED 8.5 LED warm-white 2700K ON-OFF Black 454lm

Light application



Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.