Product Code 00-7901-05-05 Installation Instructions 3D File Photometry Dialux | ULD Revit (BIM)



Punto Single Recessed

LedsC4 Team

Pendant Punto Single Recessed LED 6.5 LED warm-white 3000K 1-10V/PUSH/DALI Black 329lm

Technical features

Luminaire total power: 6.5W

Real lumens: 329 Real Im/W: 51

Correlated Colour Temperature (CCT): LED warm-white 3000K

Lens / reflector angle: MEDIUM 35°

UGR: <=16

Structure material: Aluminium

Structure finish: Black Driver Brand: HEP

Voltage / frequency: 220-240V/50-60Hz Dimming protocol: 1-10V/PUSH/DALI

Power Factor: 0.90

Useful life: 50,000h L80B20

Warranty: 5 years

Easily recyclable luminaire















Luminotechnic features


Luminance C0°G65°: 1918 Luminance C90°G65°: 1918

CRI: 90

MacAdam steps: 3 Photobiological risk: RG1

UGR		
S=0.250		
Ceiling / cavity	0.7	
Walls	0.5	
Working Plane	0.2	
Room dimensions	X=4H, Y=8H	
UGR crosswise	12.1	
UGR lengthwise	12.1	

Lampholder	Quantity	Light source power (W)	Correlated Colour Temperature (CCT)
LED	1	5W	LED warm- white 3000K








Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.



Product Code 00-7901-05-05 Installation Instructions 3D File Photometry Dialux | ULD Revit (BIM)



Punto Single Recessed

LedsC4 Team

Pendant Punto Single Recessed LED 6.5 LED warm-white 3000K 1-10V/PUSH/DALI Black 329Im		
Logistics		
x 1 Net weight (kg): 0.5 Packaged weight (kg): 0.6 Packaging: 190mm x 200mm x 95mm		

Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.