

Product Code 15-8513-DN-DN Installation Instructions 3D File Photometry Dialux | ULD Revit (BIM)



## Prolix Single

Nahtrang Studio

Spotlight Prolix Single 7.6 LED warm-white 2700K CRI 90 PHASE CUT Matte gold 217lm

## Technical features

Luminaire total power: 7.6W

Real lumens: 217 Real Im/W: 29

Correlated Colour Temperature (CCT): LED warm-white 2700K

Lens / reflector angle: FLOOD 48°

UGR: <=16

Structure material: Aluminium Structure finish: Matte gold Diffuser material: Methacrylate Diffuser finish: Transparent

Driver Brand: HEP

Voltage / frequency: 220-240V/50-60Hz

Dimming protocol: PHASE CUT

Power Factor: 0.96

Useful life: 50,000h L80B20

Warranty: 5 años

















## Luminotechnic features

TM30 RG: 100 TM30 RF: 91

Melanopic ratio: 0.511

CRI: 90

MacAdam steps: 3

Photobiological risk: RG2

UGR crosswise: 5.6 UGR lengthwise: 5.6

Lampholder	Quantity	Light source power (W)	Correlated Colour Temperature (CCT)
LED	1	5.9W	LED warm- white 2700K






Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.



Product Code 15-8513-DN-DN Installation Instructions 3D File Photometry Dialux | ULD Revit (BIM)



## Prolix Single

Nahtrang Studio

Spotlight Prolix Single 7.6 LED warm-white 2700K CRI 90 PHASE CUT Matte gold 217lm			
Logistics			
x 20  Net weight (kg): 0.63  Packaged weight (kg): 0.8  Packaging: 210mm x 125mm x 110mm			
Tuokuging. Eromin x remin x riemin			

Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.