

Product Code 15-A145-05-08 Installation Instructions 3D File Photometry Dialux | ULD Revit (BIM)



Levels Ceiling 1 Body Ø420mm

Nahtrang Studio

Ceiling fixture Levels Ceiling 1 Body Ø420mm LED 28 SW 2700-3000-4000K CASAMBI Black 2035lm

Technical features

Luminaire total power: 28W Real lumens: 2035 (3000K)

Real Im/W: 73

Correlated Colour Temperature (CCT): SW 2700-3000-4000K

Lens / reflector angle: HORIZONTAL 101°

Structure material: Steel Structure finish: Black Diffuser material: Glass Diffuser finish: Green

Voltage / frequency: 110-277V/50-60Hz

Dimming protocol: CASAMBI

Power Factor: NULL

Useful life: 50,000h L80B20

Warranty: 5 years

Easily recyclable luminaire











Luminotechnic features


CRI: 90

MacAdam steps: 3

Photobiological risk: RG1

Lampholder	Quantity	Light source power (W)
LED	1	24.4W





This product may require programming by a specialist. LedsC4 offers consulting services on control systems and programming in the factory or on-site. Ask your sales agent for more info.

Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.



Product Code 15-A145-05-08 Installation Instructions 3D File Photometry Dialux | ULD Revit (BIM)




Levels Ceiling 1 Body Ø420mm

Nahtrang Studio

Ceiling fixture Levels Ceiling 1 Body Ø420mm LED 28 SW 2700-3000-4000K CASAMBI Black 2035lm

Bluetooth range



The Bluetooth range largely depends on the obstacles and architectural features of a space, such as walls and building materials

Logistics



Net weight (kg): 3.54

Packaged weight (kg): 4.79

Packaging: 520mm x 530mm x

290mm

This product may require programming by a specialist. LedsC4 offers consulting services on control systems and programming in the factory or on-site. Ask your sales agent for more info.

Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.