
DELTALIGHT




KIX S PIN 24V 92710

REFERENCE 13529 9210 N

AVAILABLE IN
ANTHRACITE 13529 9210 N
PINE GREEN 13529 9210 PGR





View on website

General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.3
ADJUSTABILITY	180° swiveling, 360° rotatable
INFORMATION	LENS 10° INCL.1 x CABLE H05 RN-F 2 x 1 mm² 2m EXCL.LED POWER SUPPLY 24V-DC (non-dimmable or dimmable with PWM output)

Electrical info	
ELECTRICAL	24V-DC
CLASS	III
DIM TYPE	non-dimmable
ENERGY CLASS	F
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 2W / CRI>90 (R9: 55) / 2700K / 220lm
TM-30 VALUES	Rf: 91 / Rg: 99
SDCM	SDCM3
RISKGROUP	RG2
LM80	L90B10 > 150000
BEAMANGLE	10°
LED TECHNICS (LIGHT SOURCE)	220lm // 2W // 110lm/W
LED TECHNICS (LUMINAIRE)	157lm // 2,3W // 68lm/W

Requirements

LED POWER SUPPLY 24V-DC

Options

CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P

DELTALIGHT

KIX S PIN 24V 92710

13529 9210 N

For detailed installation instructions, please consult the manual : **13529_XXX0_HAND.pdf**


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 89 24 150 LED POWER SUPPLY 24V-DC / 150W — 62

Dimtype: non-dimmable


Cutout dimension (mm): 75



21012 0160 LED POWER SUPPLY 24V-DC / 24W — 10

Dimtype: non-dimmable


Cutout dimension (mm): 55



21012 0171 LED POWER SUPPLY 24V-DC / 60W DIM1 — 25

Dimtype: 1-10V


Cutout dimension (mm): 61



21012 0181 LED POWER SUPPLY 24V-DC / 90W DIM1 — 37

Dimtype: 1-10V

Cutout dimension (mm): 70




21012 0191 LED POWER SUPPLY 24V-DC / 120W DIM1 — 50

Dimtype: 1-10V

Cutout dimension (mm): 70

Miscellaneous control equipment




21032 0320 AMBIENT LIGHT SENSOR AND 24V DIMMER (PWM)

DELTALIGHT

KIX S PIN 24V 92710


13529 9210 N

Waterproof connection parts



216 12 00 CBOX

Cutout dimension (mm): 142 x 142



216 12 01 IP68 CONNECTION KIT



216 12 02 IP68 CONNECTOR 3P

Notes: