

FLOS

 F0413030 Black


Arrangements Drop Down

Designed by Michael Anastassiades, 2018



30W - 1530lm - 2700K

Diffuse light suspended lighting device. Body in extruded, curved NC-machined and black powder-coated aluminium, diffuser in platinum optical silicone. Each component can be connected to the power pack by means of an electrical and mechanical connection system designed for customisable product set-up. Roses available with two powers: lamp with power under 70W and lamp with power under 190W. Class III roses also available for installations with remote power supply: "surface" version for installations on cement, "recessed" version for plasterboard ceilings. The electronics integrated in the rose enables use of dimming systems: push, 1-10, potentiometer, DALI. In the absence of these systems, the light flow can be set with the push system included in the rose. Cable length 2.4m



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

EAN	8059607014158
Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
LED type	LED Module
Power (W)	30
System flux (lm)	1530

Physical

Colour	Black
Cord length (mm)	2500
Net weight (kg)	0.65
Package height (cm)	45
Package width (cm)	545
Package length (cm)	755
Package volume (m3)	0.02
IP internal	20

Download

Mounting instructions	 PDF
Spare Parts	 PDF

Photometric Files


LDT / IES	 LDT
-----------	-------------------------------------------------------------------------------------------

Technical Drawings

2D	 ZIP
3D	 ZIP
3D Bim	 ZIP



Schematic light drawing




Luminous flux luminaire
1530 lm

Ecodesign and Energy

Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only)
light source by a
professional


Photometric

Lighting type	Indirect, Direct
Light distribution	Symmetric
CCT (K)	2700

Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	48
LED voltage Vf (Vdc)	null
Driver	Remote
Dimmable	Yes
Dimming type	Electronic 48V
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No
Charging min time	No


Accessories & Power Supply



REQUIRED

F0416030


Arrangements Small Rose



REQUIRED

F0415030

Arrangements Big Rose



REQUIRED

F0418030

Arrangements Recessed Rose