



# **Bellhop Wall Up**

Designed by Edward Barber and Jay Osgerby, 2022




17W - 1314lm - 2700K - CRI> 90

Designed by Edward Barber and Jay Osgerby Indirect light wall lamp. Body in colored polycarbonate. Diffuser made of semi-transparent injection-moulded polycarbonate. The surface of the diffuser has been designed with a special texture to enhance the uniformity of the light distribution. High efficiency LED source with a lifetime of more than 50.000 hours. The LED source can be easily replaced on site by a professional installer when it comes to the end of its lifecycle. Bellhop Wall Up is a future-proof lamp as no glue is used to assemble its different parts. The product can therefore be separated, replaced individually, and recycled separately.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

EAN	8059607047828
Mounting	Wall
Environments	Indoor Outdoor damp location
Light source type	LED
Light sources included	Yes
LED type	LED Module
Power (W)	17
System power (W)	17
System flux (lm)	1314

### **Physical**

Colour	Grey
Length (mm)	150
Net weight (kg)	1,2
Package height (mm)	154
Package width (mm)	225
Package length (mm)	272
Package volume (m3)	0.01
IP internal	44

Mounting instructions	<b>业</b> PDF
Compatible dimmers	<b>⊥</b> PDF
Photometric Files	
LDT / IES	<b>₹</b> ZIP
Technical Drawings	5
2D	<b>⊥</b> DWG
3D	<u>↓</u> ZIP

https://professional.flos.com/en/global/product/bellhop-wall-up-f1080020/

F1080020

















**Ecodesign and Energy** 

This product contains a light source of energy efficiency

Replaceable (LED only)

light source by a professional


Labelling

class G





## Schematic light drawing



Beam	Angle:	108°
h(m)	E(lx)	D(m)
1	479	2.78
2	120	5.55
3	53	8.33
4	30	11.11
5	19	13.88

\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	1	4//	_
	2	120	į
	3	53	į
	4	30	1
479 cd	5	19	1:
nous flux <b>l</b> uminaire			
m			

### Photometric


Light distribution	Symmetric
CCT (K)	2700
CRI>	90

## Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Mains Cut Dimming

https://professional.flos.com/en/global/product/bellhop-wall-up-f1080020/

### **Spare Parts**



D1. Bellhop W Transparent Difusser RF32828

D2. LED Board for Bellhop Wall Up RF1080100





RF32828

RF1080100

Bellhop W Transparent Difusser

LED Board for Bellhop Wall Up