

# FLOS



F011A43F059.A Brass Finish/Grey Lava

## Captain Flint Outdoor H 1537 mm Brass Finish/Grey Lava

Designed by Michael Anastassiades



LED - LED array - 11W - 744lm - 4000K - CRI> 80 - Beam° 110

LED bulb included. 5-m cable with Schuko IP44 plug suitable for outdoor use. Backlit floor dimmer switch on the IP65 cable enables ON/OFF function and brightness regulation 30-100%. Casambi function on demand.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                  |                      |
|------------------|----------------------|
| Mounting         | Floor                |
| Environments     | Outdoor wet location |
| LED type         | LED array            |
| Lamp category    | LED                  |
| Ilcos            | No                   |
| Power (W)        | 11                   |
| Source flux (lm) | 1221                 |
| System flux (lm) | 744                  |

### Physical

|                         |                        |
|-------------------------|------------------------|
| Colour                  | Brass Finish/Grey Lava |
| Trim                    | No                     |
| Orientation             | Adjustable             |
| Transversal tilting (°) | 270                    |
| Net weight (kg)         | 10                     |
| IP internal             | 65                     |

### Download

[Mounting instructions](#)  ZIP

### Photometric Files

[LDT / IES](#)  ZIP

### Technical Drawings


[2D](#)  ZIP

[3D](#)  ZIP

[Bim](#)  ZIP



Schematic light drawing



Photometric


|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 4000      |
| CRI>                   | 80        |
| Beam angle C0-180 (°)  | 110       |
| Beam angle C90-270 (°) | 110       |

Electrical


|                    |                 |
|--------------------|-----------------|
| Insulation class   | II              |
| Frequency (Hz)     | 50-60           |
| Main voltage (Vac) | 220-240         |
| Driver             | Remote included |
| Dimmable           | Yes             |
| Dimming type       | Dimmer on board |
| Emergency type     | No              |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user