

FLOS



F011A44F055.A Brushed Stainless Steel/Occhio di Pernice

Captain Flint Outdoor H 1537 mm Brushed Stainless Steel/Occhio di Pernice

Designed by Michael Anastassiades



LED - LED array - 11W - 744lm - 4000K - CRI> 80 - Beam° 110

LED bulb included. 5-m cable with Schuko IP44 plug suitable for outdoor use. Backlit floor dimmer switch on the IP65 cable enables ON/OFF function and brightness regulation 30-100%. Casambi function on demand.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Floor
Environments	Outdoor wet location
LED type	LED array
Lamp category	LED
Ilcos	No
Power (W)	11
Source flux (lm)	1221
System flux (lm)	744

Physical

Colour	Brushed Stainless Steel/Occhio di Pernice
Trim	No
Orientation	Adjustable
Transversal tilting (°)	270
Net weight (kg)	10
IP internal	65

Download

Mounting instructions [ZIP](#)

Photometric Files

LDT / IES [ZIP](#)

Technical Drawings


2D [ZIP](#)

3D [ZIP](#)

[Bim](#) [ZIP](#)



Schematic light drawing



Photometric


Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	110
Beam angle C90-270 (°)	110

Electrical


Insulation class	II
Frequency (Hz)	50-60
Main voltage (Vac)	220-240
Driver	Remote included
Dimmable	Yes
Dimming type	Dimmer on board
Emergency type	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user