


FLOS



F011A21F018.A Deep Brown/Travertino Imperiale

Captain Flint Outdoor H 1537 mm Deep Brown/Travertino Imperiale

Designed by Michael Anastassiades



LED - LED array - 11W - 669lm - 2700K - CRI> 80 - Beam° 110

LED bulb included. 5-m cable with Schuko IP44 plug suitable for outdoor use. Backlit floor dimmer switch on the IP65 cable enables ON/OFF function and brightness regulation 30-100%. Casambi function on demand.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|------------------|----------------------|
| Mounting | Floor |
| Environments | Outdoor wet location |
| LED type | LED array |
| Lamp category | LED |
| Iicos | No |
| Power (W) | 11 |
| Source flux (lm) | 1099 |
| System flux (lm) | 669 |

Physical

| | |
|-------------------------|---------------------------------|
| Colour | Deep Brown/Travertino Imperiale |
| Trim | No |
| Orientation | Adjustable |
| Transversal tilting (°) | 270 |
| Net weight (kg) | 10 |
| IP internal | 65 |

Download

[Mounting instructions](#)  ZIP

Photometric Files

[LDT / IES](#)  ZIP

Technical Drawings


[2D](#)  ZIP

[3D](#)  ZIP

[Bim](#)  ZIP



Schematic light drawing



Beam Angle: 112°

| h(m) | E(lx) | D(m) |
|------|-------|-------|
| 1 | 237 | 2.95 |
| 2 | 59 | 5.91 |
| 3 | 26 | 8.86 |
| 4 | 15 | 11.81 |
| 5 | 9 | 14.76 |

Luminous flux Luminaire
669 lm

Photometric


| | |
|------------------------|-----------|
| Lighting type | Direct |
| Light distribution | Symmetric |
| CCT (K) | 2700 |
| CRI> | 80 |
| Beam angle C0-180 (°) | 110 |
| Beam angle C90-270 (°) | 110 |

Electrical


| | |
|--------------------|-----------------|
| Insulation class | II |
| Frequency (Hz) | 50-60 |
| Main voltage (Vac) | 220-240 |
| Driver | Remote included |
| Dimmable | Yes |
| Dimming type | Dimmer on board |
| Emergency type | No |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user