

FLOS



F012B02C030.A Black/Black Lava

IC F2 Outdoor H 1852 mm Black/Black Lava


Designed by Michael Anastassiades



Bulb not included. 5-m cable with Schuko IP44 plug suitable for outdoor use. Backlit floor dimmer switch on the IP65 cable enables ON/OFF function and brightness regulation 30-100% (with dimmable LED bulb).

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications


Mounting	Floor
Enviroment	Outdoor wet location
Lamp category	LED retrofit
Iicos	No

Physical

Colour	Black/Black Lava
Trim	No
Orientation	Fixed
Net weight (kg)	10
IP internal	65



Schematic light drawing



Beam Angle:	0°	
h(m)	E(lx)	D(m)
1	86	
2	21	
3	10	
4	5	
5	0	

Download

Mounting instructions [ZIP](#)

Photometric Files

LDT / IES [ZIP](#)

Technical Drawings

2D [ZIP](#)

3D [ZIP](#)

[Bim](#) [ZIP](#)

Photometric

Lighting type	Direct
Light distribution	Symmetric

Electrical

Insulation class	II
Frequency (Hz)	50-60
Main voltage (Vac)	220-240
Driver	Remote included
Dimmable	Yes
Dimming type	Dimmer on board
Emergency type	No

Notes

Bulb not included. LED: max 15W - E27

Bulbs



NOT INCLUDED

RF32288

LED Lamp E27 15W 2700K T38



NOT INCLUDED

RF32289

LED Lamp E27 15W 3000K T38