


## String Light - Sphere head - 22mt cable

Designed by Michael Anastassiades, 2014

21W - 1515lm - 2700K

Suspension lamp providing diffused light. Black, white or blue varnished die-cast aluminium body coated with clear soft-touch varnish. Optical diffuser in opal PC. Suspension system of 22 metres with Kevlar reinforced coaxial cable. Available with wall/ceiling connection in black PC and power supply with floor switch in black varnished PC. The on/off switch is electronic with optical and touch dimm mechanism included or touch dimm and CASAMBI Ready version. Dimmer included. Compulsory to add either floor switch or ceiling/wall rose.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

### Main specifications

|                   |                     |
|-------------------|---------------------|
| EAN               | 8059607041543       |
| Mounting          | Suspension          |
| Environment       | Indoor dry location |
| Light source type | LED                 |
| LED type          | LED array           |
| Power (W)         | 21                  |
| System flux (lm)  | 1515                |

### Physical

|                     |       |
|---------------------|-------|
| Colour              | White |
| Cord length (mm)    | 22000 |
| Net weight (kg)     | 1.27  |
| Package height (cm) | 300   |
| Package width (cm)  | 300   |
| Package length (cm) | 300   |
| Package volume (m3) | 0.03  |
| IP internal         | 20    |

### Download

|                       |       |
|-----------------------|-------|
| Mounting instructions | ↓ PDF |
| Mounting instructions | ↓ PDF |
| Mounting instructions | ↓ PDF |

### Photometric Files


|           |       |
|-----------|-------|
| LDT / IES | ↓ LDT |
|-----------|-------|

### Technical Drawings

|     |       |
|-----|-------|
| Bim | ↓ ZIP |
|-----|-------|




Schematic light drawing



Ecodesign and Energy  
Labelling

This product contains a light  
source of energy efficiency  
class D



Replaceable (LED only)  
light source by a  
professional

Photometric

|                    |                |
|--------------------|----------------|
| Lighting type      | Total          |
| Light distribution | Roto symmetric |
| CCT (K)            | 2700           |

Electrical

|                     |                   |
|---------------------|-------------------|
| Insulation class    | III               |
| Main voltage (Vac)  | 48                |
| Forward voltage (V) | 48                |
| Driver              | Remote excluded   |
| Dimmable            | Yes               |
| Dimming type        | Electronic 48V    |
| Dimming interface   | Dimmer Integrated |
| Batteries inside    | No                |
| Charging min time   | No                |

Accessories & Power Supply



REQUIRED

F6484009

STRING LIGHT EU FLOOR SWT  
BCO



REQUIRED

F6482009

String Light Canopy in White



OPTIONAL

F6485009

String Light Cable

Spare Parts



RF22934

Power supply unit for led




RF6480109

Kit with white hooks and white cable clamps



RF6480200

Kit with allen key and screws for ceiling rose assembly



RFU648200

Kit with allen key and screws for ceiling rose assembly